


ARMY RESEARCH LABORATORY




# Spinning Projectile Instability Induced by an Internal Mass Mounted on an Elastic Beam

Charles H. Murphy

ARL-MR-270

November 1995



19951124 020

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

DTIC QUALITY INSPECTED 1

## NOTICES

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
<small>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project(0704-0188), Washington, DC 20503.</small>				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE November 1995	3. REPORT TYPE AND DATES COVERED Final, Dec 91 - Jul 92	
4. TITLE AND SUBTITLE Spinning Projectile Instability Induced by an Internal Mass Mounted on an Elastic Beam			5. FUNDING NUMBERS PR: 1L162618AH80	
6. AUTHOR(S) Charles H. Murphy				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: AMSRL-WT-W Aberdeen Proving Ground, MD 21005-5066			8. PERFORMING ORGANIZATION REPORT NUMBER ARL-MR-270	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  The steady-state motion of a loose internal component can cause flight instabilities. In previous work, these instabilities have been predicted in terms of the amplitude and phase of the component motion. In this report, for the case of a component mounted on an elastic beam, the amplitude and phase of the motion are predicted in terms of the beam characteristics and the component's mass properties. Thus, flight stability can be computed from design parameters.				
14. SUBJECT TERMS flight stability, spinning projectile, internal mass motion			15. NUMBER OF PAGES 29	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

INTENTIONALLY LEFT BLANK.

## TABLE OF CONTENTS

		<u>Page</u>
	LIST OF FIGURES .....	v
	LIST OF TABLES .....	v
1.	INTRODUCTION .....	1
2.	EQUATIONS OF MOTION .....	2
3.	COMPONENT EQUATIONS OF MOTION .....	5
4.	DISCUSSION .....	7
5.	CONCLUSIONS .....	10
6.	REFERENCES .....	11
	APPENDIX A: EQUATIONS OF MOTION .....	13
	APPENDIX B: BEAM INFLUENCE COEFFICIENTS .....	19
	LIST OF SYMBOLS .....	25
	DISTRIBUTION LIST .....	29

Accession For		
NTIS	CRA&I	<input checked="" type="checkbox"/>
DTIC	TAB	<input type="checkbox"/>
Unannounced		<input type="checkbox"/>
Justification .....		
By .....		
Distribution /		
Availability Codes		
Dist	Avail and/or Special	
A-1		

INTENTIONALLY LEFT BLANK.

## LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1. X-Y coordinates for projectile and internal component; $x_c < 0$ .....	3
2. X-Z coordinates for projectile and internal component; $x_c < 0$ .....	3
3. Projectile damping as a function of beam stiffness for three nonpinned beam types .....	8
4. Projectile damping as a function of beam stiffness for three pinned beam types .....	8
5. Component cant and deflection as functions of beam stiffness for a fixed-fixed beam .....	9
6. Projectile damping as a function of beam damping for a fixed-fixed beam and three types of damping; $\hat{E}I/\hat{E}I^* = 0.1$ .....	9
7. Projectile damping as function of coming frequency for three nonpinned beam types .....	10

## LIST OF TABLES

<u>Table</u>	<u>Page</u>
1. Influence Coefficients for Various Beams .....	6
2. Test Case Values .....	7

INTENTIONALLY LEFT BLANK.

## 1. INTRODUCTION

In the mid 1950s four shell types exhibited unusual behavior that involved the movement of their interior parts (Boyer 1955a, 1955b; Roecker and Boyer 1957; Karpov and Bradley 1958). In 1977 a simple theory was developed to relate the motion of internal parts to the angular motion of the spinning projectile (Murphy 1977). This theory assumed a circular lateral motion of the internal component combined with a coning motion of its axis of symmetry. Both of these motions are at a coning frequency of the spinning shell. The frequency of the internal motion was assumed to be the fast frequency of the projectile's free angular motion, the amplitude was set by the available tolerances, and the phase of the motion was induced by internal friction.

The theory predicted a destabilizing side moment and a spin-up moment equal to the product of the side moment and the magnitude of the projectile's angular motion. Later it was shown that this relation between side moment and spin moment is valid for any steady motion of an internal payload (Murphy 1989). For 60° phase angles, all observed instabilities could be explained by the measured clearances and the measured despins of the unstable projectiles were in good quantitative agreement with the theory's prediction.

The theory, however, made no attempt to predict the amplitude and phase of the internal motion. For a mass supported by an elastic internal beam, W. R. Chadwick (1975) did develop a complete theory for the combined motion of the internal mass and the projectile. Unfortunately, this work was marred by two errors in the proper treatment of beam damping, and his equations did not predict flight results.

In this report,\* we develop the correct equations of motion for the projectile and its internal, beam-supported mass. Using Chadwick's influence coefficients, we compute the elastic response of various beams with a proper expression for beam damping. The beams considered are forward-facing and rearward-facing cantilever beams, fixed-pinned beams, and fixed-fixed beams.

The theory and associated computer runs show that the instabilities induced by beam-mounted masses are strongly controlled by beam elastic characteristics and, very importantly, the form and amplitude of

---

\* A shorter version of this report has appeared as an AIAA preprint (Murphy 1992).

the beam damping. Small beam damping has little effect on projectile flight stability, but moderate damping can cause instability when the beam is sufficiently soft.

The inertia properties of the internal mass determine the relative importance of beam deflection or beam cant on projectile stability. Theory indicates design tradeoffs for beam characteristics and mass inertial properties.

## 2. EQUATIONS OF MOTION

In Murphy (1977), the internal component is assumed to perform a known lateral and angular motion. In complex notation, the lateral motion is described in nonspinning coordinates by

$$y_c + iz_c = \ell E, \quad (1)$$

and the angular motion is described by the component's axis of symmetry orientation angles with respect to the projectile's axis of symmetry:

$$\gamma_y + i\gamma_z = \Gamma. \quad (2)$$

The projectile's motion relative to its flight path is given by its angles of attack and sideslip in nonrolling coordinates:

$$\tilde{\beta} + i\tilde{\alpha} = \tilde{\xi}. \quad (3)$$

These geometrical quantities are shown in Figures 1 and 2. The usual linear analysis yields the following equation for the projectile's motion:

$$I_t \ddot{\tilde{\xi}} - (A_q + iL_x) \dot{\tilde{\xi}} - (A_\alpha + iA_{p\alpha}) \tilde{\xi} = B_\epsilon \ddot{E} + I_{tc} \ddot{\Gamma} - i p_c I_{xc} \dot{\Gamma}. \quad (4)$$

The angular motion of a solid projectile ( $E = \Gamma = 0$ ) is usually described as the sum of two coning motions of the form

$$\tilde{\xi} = \sum_{j=1,2} K_j e^{i\phi_j}, \quad (5)$$

$$\dot{\phi}_j = \frac{L_x}{2I_t} \left[ 1 \pm \sqrt{1 - 1/s_g} \right], \quad (6)$$




Figure 1. X-Y coordinates for projectile and internal component;  $x_c < 0$ .




Figure 2. X-Z coordinates for projectile and internal component;  $x_c < 0$ .

$$s_g = \frac{L_x^2}{4 I_t A_\alpha}, \quad (7)$$

and

$$\frac{\dot{K}_j}{K_j} = \lambda_j = \frac{\dot{\phi}_j A_q + A_p \alpha}{2 \dot{\phi}_j I_t - L_x}. \quad (8)$$

Since the fast mode is usually the one adversely affected by payload motion, a simple one-mode motion is assumed, and the internal component is assumed to perform constant-amplitude motion at the fast frequency.

$$\Gamma = \gamma e^{i(\phi_1 + \phi_\gamma)} \quad (9)$$

and

$$E = \epsilon e^{i(\phi_1 + \phi_\epsilon)}. \quad (10)$$

When equations 9–10 are substituted in equation 4, it can be shown that the frequency and damping of the fast mode are changed by the following amounts:

$$\Delta \dot{\phi}_1 = \frac{-\dot{\phi}_1 C_1}{K_1 (2 I_t \dot{\phi}_1 - L_x)} \quad (11)$$

and

$$\Delta \lambda_1 = \frac{\dot{\phi}_1 S_1}{K_1 (2 I_t \dot{\phi}_1 - L_x)}, \quad (12)$$

where

$$C_1 = B_\gamma \gamma \cos \phi_\gamma - B_\epsilon \dot{\phi}_1 \epsilon \cos \phi_\epsilon$$

$$S_1 = B_\gamma \gamma \sin \phi_\gamma - B_\epsilon \dot{\phi}_1 \epsilon \sin \phi_\epsilon$$

$$B_\gamma = I_{xc} p_c - I_{tc} \dot{\phi}_1$$

$$B_\epsilon = m_c x_c \ell.$$

$\gamma$  and  $\epsilon$  and their phase angles were estimated from available clearances and good engineering predictions were obtained. In this report, we will predict these quantities for a component mounted on an elastic beam.

### 3. COMPONENT EQUATIONS OF MOTION

The lateral motion of an internal component can be described in a nonrolling coordinate system whose x-axis is aligned along the projectile's axis of symmetry. The angular velocity of these coordinates can be specified by

$$Q = \dot{\theta} + i\dot{\psi}.$$

The lateral motion of the component can be easily expressed in terms of the transverse components of the force and moment exerted by the beam on the component:\*

$$m_c \left[ \ell \ddot{E} + V \left( \dot{\xi} - iQ \right) - i x_c \dot{Q} \right] = F_{yc} + i F_{zc} \quad (13)$$

and

$$I_{tc} (\ddot{\Gamma} - i\dot{Q}) - i p_c I_{xc} (\dot{\Gamma} - iQ) = - (M_{yc} + i M_{zc}). \quad (14)$$

The elastic part of the beam force and moment can be computed by simple beam theory to be a linear function of  $E$  and  $\Gamma$ . For the coning motion of equations 9-10,

$$[F_{yc} + i F_{zc}]_{\text{elastic}} = [b_{11} \ell \epsilon e^{i\phi_\epsilon} + b_{12} \gamma e^{i\phi_\gamma}] e^{i\phi_1} \quad (15)$$

and

$$[M_{yc} + i M_{zc}]_{\text{elastic}} = i [b_{21} \ell \epsilon e^{i\phi_\epsilon} + b_{22} \gamma e^{i\phi_\gamma}] e^{i\phi_1}, \quad (16)$$

---

\* See Appendix A for derivation of Equations 13-14. Appendix B outlines the derivation of Table 1.

where  $b_{12} = b_{21}$  and the linear coefficients,  $b_{ij}$ , can be computed for a variety of beam supports by taking the matrix inverse of the influence coefficients,  $a_{ij}$ , given in Table 1.

The effect of beam damping can be approximated by linear terms in the derivatives of  $E$  and  $\Gamma$ . Since the beam is spinning with the projectile, these derivatives must be taken in projectile-fixed coordinates

Table 1. Influence Coefficients for Various Beams

Type	$a_{11}\hat{E}I$	$a_{21}\hat{E}I$	$a_{22}\hat{E}I$
Fixed-fixed	$\frac{a^3b^3}{3(a+b)^3}$	$-\frac{a^2b^2(a-b)}{2(a+b)^3}$	$\frac{ab(a^2+b^2-ab)}{(a+b)^3}$
Fixed-pinned	$\frac{a^3b^2(3a+4b)}{12(a+b)^3}$	$\frac{a^2b(2b^2-a^2)}{4(a+b)^3}$	$\frac{a(a^3+4b^3)}{4(a+b)^3}$
Pinned-fixed	$\frac{a^2b^3(4a+3b)}{12(a+b)^3}$	$\frac{ab^2(b^2-2a^2)}{4(a+b)^3}$	$\frac{b(4a^3+b^3)}{4(a+b)^3}$
Fixed-free	$\frac{a^3}{3}$	$\frac{a^2}{2}$	$a$
Free-fixed	$\frac{b^3}{3}$	$-\frac{b^2}{2}$	$b$
Pinned-pinned	$\frac{a^2b^2}{3(a+b)}$	$\frac{ab(b-a)}{3(a+b)}$	$\frac{a^2+b^2-ab}{3(a+b)}$

that are spinning with respect to earth-fixed axes. A coning frequency  $\dot{\phi}_1$  in the nonspinning system would appear in a spinning system as  $\dot{\phi}_1 - p$  where  $p$  is the projectile spin. The beam damping can be inserted in equation (15) by replacing  $b_{11}$  by  $b_{11}[1 + i d_e(\dot{\phi}_1 - p)p^{-1}]$  and in equation (16) by replacing  $b_{22}$  by  $b_{22}[1 + i d_\gamma(\dot{\phi}_1 - p)p^{-1}]$ .

If the small effect of the lift force is neglected,

$$\ddot{\xi} = iQ. \quad (17)$$

Equations 13–16 can be combined to yield

$$\left[ \dot{\phi}_1^2 m_c + b_{11} \left[ 1 + i d_\epsilon (\dot{\phi}_1 - p) p^{-1} \right] \right] \ell \epsilon e^{i\phi_\epsilon} + b_{12} \gamma e^{i\phi_\gamma} = m_c x_c (\dot{\phi}_1)^2 K_1 \quad (18)$$

and

$$\begin{aligned} b_{21} \ell \epsilon e^{i\phi_\epsilon} + \left[ -\dot{\phi}_1 B_\gamma + b_{22} \left[ 1 + i d_\gamma (\dot{\phi}_1 - p) p^{-1} \right] \right] \gamma e^{i\phi_\gamma} \\ = -i \dot{\phi}_1 B_\gamma K_1. \end{aligned} \quad (19)$$

When beam parameters, component inertia properties, and coning motion parameters are inserted in equations 18–19, amplitude and phase angles of the component motion can be determined. From these, the stability of the coning motion follows from equation 12.

#### 4. DISCUSSION

To illustrate these results, we will consider an 8-in projectile with a particular rotationally symmetric internal component. The appropriate physical and aerodynamic properties of this projectile and its component are given in Table 2. The nominal value of the beam's stiffness is given as  $\hat{E}I^* = 59,800 \text{ lb/ft}^2$ . In Figures 3 and 4, the projectile damping is plotted as a function of beam elasticity for all six possible beam types. When the beam stiffness is reduced to 10% of the Table 2 value, all beam types can cause flight instability.

Table 2. Test Case Values

a	= 0.50 ft	d	= $d_\epsilon = d_\alpha = 0.5$
b	= 1.16 ft	$\hat{E}I^*$	= 59,800 lb/ft <sup>2</sup>
$I_{xb}$	= 0.240 slug/ft <sup>2</sup>	$I_{xc}$	= 0.130 slug-ft <sup>2</sup>
$I_{tb}$	= 2.306 slug/ft <sup>2</sup>	$I_{tc}$	= 0.700 slug-ft <sup>2</sup>
$m_b$	= 20 slug	$m_c$	= 2.6 slug
$\ell$	= 8 in	$x_c$	= -0.3 ft
$C_{m_\alpha}$	= 5	$\lambda_{10}$	= -0.33 1/s
$C_{n_\alpha}$	= 1.8	p	= 637 rad/s
$\rho$	= 0.002 slug/ft <sup>3</sup>	V	= 1,200 ft/s




Figure 3. Projectile damping as a function of beam stiffness for three nonpinned beam types.




Figure 4. Projectile damping as a function of beam stiffness for three pinned beam types.

In Figure 5, the size of the component motion is plotted as a function of beam stiffness for the fixed-fixed beam. For small coning motion ( $K_1 < 0.1$ ), this motion is quite small and only the relatively large value assigned to  $I_c$  causes this motion to induce flight instability.




Figure 5. Component cant and deflection as functions of beam stiffness for a fixed-fixed beam.

Figure 6 shows the beam damping effect on flight stability for the fixed-fixed beam with  $\hat{EI}/\hat{EI}^* = 0.1$ . The nominal value of  $d = 0.5$  is shown for the equal damping curve  $d_\epsilon = d_\gamma = d$ . The other two curves consider the solo effects of continued damping ( $d_\gamma$ ) and of deflection damping ( $d_\epsilon$ ), respectively. Clearly, cant damping can have a greater adverse effect, and 0.5 is the worst value for  $d_\epsilon = d_\gamma$ .




Figure 6. Projectile damping as a function of beam damping for a fixed-fixed beam and three types of damping;  $\hat{EI}/\hat{EI}^* = 0.1$ .

Intuitively, one might think the instabilities shown by Figures 3 and 4 are due to reducing the natural frequency of the beam to the coning frequency of the projectile. In Figure 7, the natural beam frequency,  $\omega_e$ , of the three beam types of Figure 3 is computed, and the projectile damping is plotted as a function of  $\dot{\phi}_1/\omega_e$ . For the fixed-fixed beam, instability occurs when the coning frequency is only 10% of the beam frequency!




Figure 7. Projectile damping as function of coning frequency for three nonpinned beam types.

## 5. CONCLUSIONS

- (1) The steady-state motion of internal mass on an elastic beam can be computed.
- (2) For appropriate values of beam damping, flight instabilities can be predicted.
- (3) These instabilities can occur for frequencies less than 10% of the beam natural frequency.

## 5. REFERENCES

- Boyer, E. D. "Comparison of Aerodynamic Characteristics of 20-mm HEI Shell M97 With Fuze M75 and 20-mm Shell T216E1 With Fuze M505." BRL-MR-865, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, April 1955a.
- Boyer, E. D. "Aerodynamic Characteristics for Small Yaws of 20-mm Shell, HEI, T282E1 With Fuze M505 for Mach Numbers .36 to 3.78." BRL-MR-916, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, August 1955b.
- Chadwick, W. R. "Stability of Spinning Shell." Unpublished NSWC Report, Naval Surface Weapons Center, Dahlgren, VA, September 1975.
- Karpov, B. G., and J. W. Bradley. "A Study of Causes of Short Range of the 8-in T317 Shell." BRL-R-1049, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, May 1958.
- Murphy, C. H. "Influence of Moving Internal Parts on Angular Motion of Spinning Projectiles." Journal of Guidance and Control, vol. 1, pp. 117-122, March-April 1978. (See also BRL-MR-2731, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, February 1977.)
- Murphy, C. H. "A Symptom of Payload-Induced Flight Instability." Journal of Guidance, Control, and Dynamics, vol. 12, pp. 771-776, 1989. (See also BRL-MR-3867, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, September 1989.)
- Murphy, C. H. "Spinning Projectile Instability Induced by an Internal Mass Mounted on an Elastic Beam." AIAA-92-4493, AIAA Atmospheric Flight Mechanics Conference, August 1992.
- Roecker, E. T., and E. D. Boyer. "Aerodynamic Characteristics of 30-mm HEI Shell, T306E10." BRL-MR-1098, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, August 1957.

INTENTIONALLY LEFT BLANK.

APPENDIX A:  
EQUATIONS OF MOTION

INTENTIONALLY LEFT BLANK.

The complete projectile is assumed to consist of a body with mass  $m_b$  and an internal component of mass  $m_c$  mounted on an elastic massless beam. The total mass of the projectile is  $m = m_c + m_b$ . The center of mass (CM) of the internal component is located a distance  $x_c$  from the CM of the projectile, and the CM of the body is a distance  $x_b$  from the CM of the projectile ( $m_b x_b + m_c x_c = 0$ ). If  $I_{tc}$  is the transverse moment of inertia of the component relative to its CM and  $I_{tb}$  is the transverse moment of inertia of the body relative to its CM, then  $I_t$ , the transverse moment of inertia of the projectile relative to its CM, is given by

$$I_t = I_{tb} + m_b x_b^2 + I_{tc} + m_c x_c^2. \quad (A-1)$$

The projectile's axis of symmetry can be located relative to fixed axes by its pitch and yaw angles,  $\theta$  and  $\Psi$ , and its orientation relative to the velocity vector can be defined by its angles of attack and sideslip,\*  $\tilde{\alpha}$  and  $\tilde{\beta}$ . The internal component is assumed to be a cylinder or disk whose axis is located relative to the projectile's axis by the angles  $\gamma_y$  and  $\gamma_z$ . The transverse displacement of the component CM relative to the body's axis of symmetry is specified by the displacements  $y_c$  and  $z_c$ . All these geometrical quantities are shown in Figures 1 and 2.

The projectile has lateral aerodynamic forces and moments acting on it, represented by  $F_y$ ,  $F_z$  and  $M_y$ ,  $M_z$ , respectively. The elastic beam exerts forces and moments on the internal component when it is deflected; these are represented by  $F_{yc}$ ,  $F_{zc}$ , and  $M_{yc}$ ,  $M_{zc}$ , respectively. For simplicity, aerodynamic drag is neglected and all angles are assumed to be small.

The equations of motion of the projectile body and internal component are as follows:

$$m_b [V (\ddot{\tilde{\beta}} + \dot{\Psi}) + x_b \ddot{\Psi}] = F_y - F_{yc}, \quad (A-2)$$

---

\* The tilde superscripts are used to indicate that these angles are measured in nonspinning coordinates and not the usual missile-fixed coordinates.

$$m_b [V (\ddot{\alpha} - \dot{\theta}) - x_b \ddot{\theta}] = F_z - F_{zc}, \quad (A-3)$$

$$I_{tb} \ddot{\theta} + p_b I_{xb} \dot{\psi} = M_y - M_{yc} + x_b F_z + (x_c - x_b) F_{zc}, \quad (A-4)$$

$$I_{tb} \ddot{\psi} - p_b I_{xb} \dot{\theta} = M_z - M_{zc} - x_b F_y - (x_c - x_b) F_{yc}, \quad (A-5)$$

$$m_c [\ddot{y}_c + V(\dot{\beta} + \dot{\psi}) + x_c \ddot{\psi}] = F_{yc}, \quad (A-6)$$

$$m_c [\ddot{z}_c + V(\dot{\alpha} - \dot{\theta}) - x_c \ddot{\theta}] = F_{zc}, \quad (A-7)$$

$$I_{tc} (\ddot{\theta} - \ddot{\gamma}_z) + p_c I_{xc} (\dot{\psi} + \dot{\gamma}_y) = M_{yc}, \quad (A-8)$$

and

$$I_{tc} (\ddot{\psi} + \ddot{\gamma}_y) - p_c I_{xc} (\dot{\theta} - \dot{\gamma}_z) = M_{zc}, \quad (A-9)$$

where  $I_{xb}$  and  $I_{xc}$  are the axial moments of inertia of the body and component, respectively.

The transverse force on the component can be eliminated between equations (A-2)–(A-3) and (A-6)–(A-7), and complex variables can be introduced to yield the following force equation for the projectile:

$$mV (\ddot{\xi} - iQ) = F_y + iF_z - m_c \ell \ddot{E}, \quad (A-10)$$

where

$$\tilde{\xi} = \tilde{\beta} + i \tilde{\alpha},$$

$$Q = \dot{\theta} + i \dot{\psi},$$

and

$$E = (y_c + i z_c) \ell^{-1}.$$

The external aerodynamic force can be approximated by the linear normal force, and the small component inertia force can be neglected to yield the simple relation

$$m V (\dot{\tilde{\xi}} - i Q) = - F_N \tilde{\xi}, \quad (A-11)$$

where

$$F_N = (1/2) \rho V^2 S C_{N\alpha}.$$

Equations (A-2)–(A-9) can now be combined to eliminate the transverse forces and moments acting on the internal component. The resulting moment equation for the projectile is

$$I_t \dot{Q} - i L_x Q = M_y + i M_z - i B_\epsilon \ddot{E} - i I_{tc} \ddot{\Gamma} - p_c I_{xc} \dot{\Gamma}, \quad (A-12)$$

where

$$L_x = p_b I_{xb} + p_c I_{xc},$$

$$B_\epsilon = m_c x_c \ell,$$

and

$$\Gamma = \gamma_y + i \gamma_z.$$

The external aerodynamic moment can be replaced by the usual linear moment expansion and Q can be eliminated by the use of equation (A-11) to yield the following form of the projectile moment equation:

$$I_t \ddot{\xi} - (A_q + i L_x) \dot{\xi} - (A_\alpha + i A_{p\alpha}) \tilde{\xi} - B_\epsilon \ddot{\epsilon} - I_{tc} \ddot{\Gamma} + i p_c I_{xc} \dot{\Gamma} = 0, \quad (A-13)$$

where

$$A_q = (1/2) \rho S \ell^2 V \left[ C_{Mq} + C_{M\dot{\alpha}} - k_t^2 C_{N\alpha} \right],$$

$$A_\alpha = (1/2) \rho S \ell V^2 C_{M\alpha},$$

and

$$A_{p\alpha} = (1/2) \rho S \ell^2 V p_b \left[ C_{Mp\alpha} + k_a^2 C_{N\alpha} \right].$$

The complex equations for the motion of the internal component can be written from equations (A-6)–(A-9) as follows:

$$m_c \left[ \ell \ddot{\epsilon} + V \left( \dot{\xi} - i Q \right) - i x_c \dot{Q} \right] = F_{yc} + i F_{zc} \quad (A-14)$$

and

$$I_{tc} (\ddot{\Gamma} - i \dot{Q}) - i p_c I_{xc} (\dot{\Gamma} - i Q) = -i (M_{yc} + i M_{zc}). \quad (A-15)$$

The motion of the internal component is determined by equations (A-11), (A-14), and (A-15) when the component forces and moments are specified and the projectile motion is known.

**APPENDIX B:**  
**BEAM INFLUENCE COEFFICIENTS**

INTENTIONALLY LEFT BLANK.

If a mass is mounted on an elastic beam and the beam is deformed, the beam exerts a force and moment on the mass. The components of this force and moment appear in equations (A-14) and (A-15) and it is necessary to express these quantities as functions of the displacement ( $\epsilon_y, \epsilon_z$ ) and rotation ( $\gamma_y, \gamma_z$ ) of the mass. For an elastic beam, these are linear relations:

$$F_{yc} + i F_{zc} = b_{11} \ell E + b_{12} \Gamma \quad (\text{B-1})$$

and

$$M_{yc} + i M_{zc} = i (b_{21} \ell E + b_{22} \Gamma), \quad (\text{B-2})$$

where  $b_{12} = b_{21}$ .

For simple beam theory, it is easy to express the displacement and rotation as functions of applied force and moment ( $F_a, M_a$ ). In the xy plane, this yields the following linear relations in terms of the beam influence coefficients:

$$\ell \epsilon_y = a_{11} F_a + a_{12} M_a \quad (\text{B-3})$$

and

$$\gamma_y = a_{21} F_a + a_{22} M_a. \quad (\text{B-4})$$

$F_a$  and  $M_a$  are the negatives of the corresponding force and moment on the internal component ( $F_{yc}, M_{zc}$ ). Thus, by equations (B-1) to (B-4), the  $b_{ij}$ 's are related to the  $a_{ij}$ 's as follows:

$$b_{11} = -\frac{a_{22}}{D}, \quad (\text{B-5})$$

$$b_{21} = b_{12} = \frac{a_{12}}{D}, \quad (\text{B-6})$$

$$b_{22} = -\frac{a_{11}}{D}, \quad (\text{B-7})$$

and

$$D = a_{22} a_{11} - (a_{12})^2. \quad (\text{B-8})$$

We will assume the beam has a length  $a + b$ ; the internal component and its associated applied force and moment are located a distance  $a$  from the forward end of the beam and a distance  $b$  from its rear end.

The influence coefficients can be computed for various beams by means of the well-known elastic beam equation:

$$\hat{E} I \frac{d^2 y}{d x^2} = -M_z(x), \quad (\text{B-9})$$

where

$$\begin{aligned} M_z &= -x F_{y0} + M_{z0} & 0 \leq x < a \\ &= -x F_{y0} + M_{z0} - (x - a) F_a + M_a & a \leq x \leq a + b \\ &= -M_{z1} & x = a + b \end{aligned} \quad (\text{B-10})$$

and

$$F_{y0} + F_{y1} = -F_a, \quad (\text{B-11})$$

where  $\hat{E}$  is Young's modulus,  $I$  is the area moment of inertia,  $(M_{z0}, M_{z1})$  and  $(F_{y0}, F_{y1})$  are the moments and forces exerted on the ends of the beam.

Three possible constraints are considered at each end of the beam. At the front end,  $x = 0$ , these are:

$$\text{(a) free} \quad F_{y0} = 0 ; \quad M_{z0} = 0$$

$$\text{(b) pinned} \quad y_0 = 0$$

and

$$\text{(c) fixed} \quad y_0 = 0 ; \quad \frac{dy(0)}{dx} = 0.$$

Similar conditions can be assigned to the rear end,  $x = a + b$ . The values of the influence coefficients are given in Table 1 for six combinations of end conditions: fixed-fixed, fixed-pinned, pinned-fixed, fixed-free, free-fixed, and pinned-pinned. The construction of this table can be illustrated by considering the rearward-facing cantilever case. For this case,  $F_{y0} = -F_a$ ,  $M_{z0} = -M_a - aF_a$  (i.e., the beam is fixed-free). Equation (B-9) can be integrated twice to yield

$$\begin{aligned}\hat{E}I \frac{dy}{dx} &= -\frac{x(x-2a)}{2} F_a + xM_a & 0 \leq x < a \\ &= \frac{a^2}{2} F_a + aM_a & a \leq x \leq a + b\end{aligned}\quad (B-12)$$

and

$$\begin{aligned}\hat{E}I y &= \frac{-x^2(x-3a)}{6} F_a + \frac{x^2}{2} M_a & 0 \leq x < a \\ &= \frac{a^2(3x-a)}{6} F_a + \frac{a(2x-a)}{2} M_a & a \leq x \leq a + b.\end{aligned}\quad (B-13)$$

At  $x = a$ , equations (B-12) and (B-13) become

$$\hat{E}I y(a) = \hat{E}I \epsilon_y = \frac{a^3}{3} F_a + \frac{a^2}{2} M_a \quad (B-14)$$

and

$$\hat{E}I \frac{dy(a)}{dx} = \hat{E}I \gamma_y = \frac{a^2}{2} F_a + aM_a. \quad (B-15)$$

The above coefficients of  $F_a$  and  $M_a$  are precisely those given by the fixed-free entries in Table 1. The other coefficients can be computed in a similar manner.

INTENTIONALLY LEFT BLANK.

# LIST OF SYMBOLS

$A_{p\alpha}$	$(1/2)\rho S\ell^2 V p_b [C_{M_{p\alpha}} + k_a^2 C_{N_\alpha}]$
$A_q$	$(1/2)\rho S\ell^2 V [C_{M_q} + C_{M_{\dot{\alpha}}} - k_t^2 C_{N_\alpha}]$
$A_\alpha$	$(1/2)\rho S\ell V^2 C_{M_\alpha}$
$a$	distance from the forward end of the beam to the internal component
$a_{ij}$	beam influence coefficients; Table 1
$B_\gamma$	$I_{xc} p_c - I_{tc} \dot{\phi}_1$
$B_\epsilon$	$m_c x_c \ell$
$b$	distance from the rear end of the beam to the internal component
$b_{ij}$	beam coefficients derived from the $a_{ij}$ 's.
$C_{M_{p\alpha}}$	Magnus moment coefficient
$C_{M_q} + C_{M_{\dot{\alpha}}}$	sum of the damping moment coefficients
$C_{M_\alpha}$	static moment coefficient
$C_{N_\alpha}$	normal force coefficient
CM	center of mass
$d_\gamma$	nondimensional beam damping orientation coefficient, equation (19)
$d_\epsilon$	nondimensional beam damping displacement coefficient, equation (18)
$E$	$(y_c + iz_c)/\ell$
$\hat{E}$	Young's modulus
$F_{yc}, F_{zc}$	lateral components of the force exerted by the elastic beam on the component

$I_x, I_t$	axial and transverse moments of inertia of the total projectile relative to its CM
$I_{xb}, I_{tb}$	axial and transverse moments of inertia of the body relative to its CM
$I_{xc}, I_{tc}$	axial and transverse moments of inertia of the component relative to its CM
$K_j$	$ \tilde{\xi} $
$k_a$	$\sqrt{I_x/m_\ell^2}$ , the axial radius of gyration
$k_t$	$\sqrt{I_t/m_\ell^2}$ , the transverse radius of gyration
$L_x$	$p_b I_{xb} + p_c I_{xc}$
$\ell$	reference length
$M_{yc}, M_{zc}$	lateral components of the moment exerted by the elastic beam on the component
$m$	$m_b + m_c$
$m_b$	mass of the body
$m_c$	mass of the component
$p$	projectile spin rate
$p_b$	body spin rate
$p_c$	component spin rate
$Q$	$\dot{\theta} + i\dot{\psi}$
$S$	$\pi\ell^2/4$ , reference area
$s_g$	gyroscopic stability factor, equation (7)
$t$	time
$V$	projectile velocity
$x$	axial distance, measured positive rearward, where $x = 0$ at the forward end of the beam, $x = a$ at the component, and $x = a + b$ at the rear end of the beam
$x_b$	distance from the CM of the (body + component) to the CM of the body

$x_c$	distance from the CM of the (body + component) to the CM of the component, where $m_b x_b + m_c x_c = 0$
$y_c, z_c$	transverse displacements of the component CM relative to the body's axis of symmetry
$\tilde{\alpha}, \tilde{\beta}$	the projectile's angles of attack and sideslip in a nonrolling system
$\Gamma$	$\gamma_y + i \gamma_z$
$\gamma$	$ \Gamma $
$\gamma_y, \gamma_z$	orientation angles defining the component axis of symmetry with respect to the projectile axis of symmetry
$\varepsilon$	$ E $
$\dot{\theta}$	projectile pitch rate
$\lambda_1$	$\dot{K}_1/K_1$ , a damping coefficient
$\tilde{\xi}$	$\tilde{\beta} + i \tilde{\alpha}$
$\rho$	air density
$\phi_1$	polar angle of $\tilde{\xi}$
$\dot{\phi}_1$	fast coning frequency
$\phi_\gamma$	$\Gamma$ phase angle, equation (9)
$\phi_\varepsilon$	$E$ phase angle, equation (10)
$\dot{\psi}$	projectile yaw rate
$\omega_\xi$	natural frequency of beam
$(\dot{\phantom{x}})$	$d(\phantom{x})/dt$

INTENTIONALLY LEFT BLANK.

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
2	DEFENSE TECHNICAL INFO CTR ATTN DTIC DDA 8725 JOHN J KINGMAN RD STE 0944 FT BELVOIR VA 22060-6218

1	DIRECTOR US ARMY RESEARCH LAB ATTN AMSRL OP SD TA 2800 POWDER MILL RD ADELPHI MD 20783-1145
---	---

3	DIRECTOR US ARMY RESEARCH LAB ATTN AMSRL OP SD TL 2800 POWDER MILL RD ADELPHI MD 20783-1145
---	---

1	DIRECTOR US ARMY RESEARCH LAB ATTN AMSRL OP SD TP 2800 POWDER MILL RD ADELPHI MD 20783-1145
---	---

ABERDEEN PROVING GROUND

5	DIR USARL ATTN AMSRL OP AP L (305)
---	---------------------------------------

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	COMMANDER US ARMY ARDEC ATTN SMCAR AET A MR JOHN M WHYTE BLDG 3342 PICATINNY ARSNL NJ 07806-5000	1	DIRECTOR SANDIA NATIONAL LABORATORIES ATTN DR WILLIAM OBERKAMPF DIVISION 1636 P O BOX 580 ALBUQUERQUE NM 87185
1	COMMANDER US ARMY ARDEC ATTN TECHNICAL LIBRARY PICATINNY ARSNL NJ 07806-5000	1	DIRECTOR SANDIA NATIONAL LABORATORIES ATTN DR WALTER WOLFE ALBUQUERQUE NM 87185
1	COMMANDER US ARMY CECOM ATTN ASQNC ELC I T MYER CENTER R&D TECHNICAL LIBRARY FT MONMOUTH NJ 07703-5301	1	MASSACHUSETTS INST OF TECHNOLOGY DEPT OF AERONAUTICS & ASTRONAUTICS ATTN PROF EUGENE E COVERT 77 MASSACHUSETTS AVE CAMBRIDGE MA 02139
1	DIRECTOR US ARMY MSIC ATTN AIAMS YDL REDSTONE ARSNL AL 35898-5500	1	UNIVERSITY OF VIRGINIA DEPT OF ENGRG SCIENCE & SYSTEMS ATTN PROF IRA D JACOBSON THORNTON HALL CHARLOTTESVILLE VA 22904
10	CENTRAL INTELLIGENCE AGENCY OFFICE OF CENTRAL REFERENCE DISSEMINATION BRANCH ROOM GE 47 HQS WASH DC 20505	1	THE AEROSPACE CORPORATION ATTN DR DANIEL H PLATUS 2350 E EL SEGUNDO BOULEVARD EL SEGUNDO CA 90245
1	AIR FORCE ARMAMENT LABORATORY AERODYNAMICS BRANCH ATTN GERALD WINCHENBACH EGLIN AFB FL 32542-5434	1	ARROW TECHNOLOGY ASSOCIATES INC ATTN MR ROBERT H WHYTE P O BOX 4218 S BURLINGTON VT 05401-0042
1	COMMANDER US NAVAL SURFACE WARFARE CENTER ATTN DR WILLIAM R CHADWICK DAHLGREN VA 22448		<u>ABERDEEN PROVING GROUND</u>
1	COMMANDER US NAVAL SURFACE WARFARE CENTER ATTN DR THOMAS R PEPITONE MAIL STOP M/C K21 DAHLGREN VA 22448	4	USARL ATTN: AMSRL-WT, DR. I. MAY DR. J. ROCCHIO AMSRL-WT-W, DR. C. MURPHY AMSRL-WT-WB, DR. W. D'AMICO
1	DIRECTOR SANDIA NATIONAL LABORATORY ATTN MR A E HODAPP DIVISION 1331 ALBUQUERQUE NM 87185	1	CDR USA ARDEC ATTN: AMSTA-AR-FSF-T, MR. R. F. LIESKE BLDG 120
		1	CDR USA ERDEC ATTN: SCDRD-RTM, MR. M. C. MILLER BLDG E5951 APG-EA

NO. OF  
COPIES ORGANIZATION

1 DEFENSE RESEARCH CENTER - SALISBURY  
ATTN DR RUSSELL L POPE  
BOX 2151 GPO  
ADELAIDE S AUSTRALIA 5001

INTENTIONALLY LEFT BLANK.

## USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. ARL Report Number ARL-MR-270 Date of Report November 1995

2. Date Report Received \_\_\_\_\_

3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

CURRENT  
ADDRESS

\_\_\_\_\_  
Organization

\_\_\_\_\_  
Name

\_\_\_\_\_  
Street or P.O. Box No.

\_\_\_\_\_  
City, State, Zip Code

7. If indicating a Change of Address or Address Correction, please provide the Current or Correct address above and the Old or Incorrect address below.

OLD  
ADDRESS

\_\_\_\_\_  
Organization

\_\_\_\_\_  
Name

\_\_\_\_\_  
Street or P.O. Box No.

\_\_\_\_\_  
City, State, Zip Code

(Remove this sheet, fold as indicated, tape closed, and mail.)  
(DO NOT STAPLE)